

WestRock Tango® C2S

Product Guide



Some resumes tell a story before anything's ever printed on them

Your print job is in good hands with Tango C2S. This premium 92 bright Solid Bleached Sulfate (SBS) paperboard is coated on both sides, plus it has an added ingredient not found in other SBS products: a proven reputation for outstanding runnability, printability and consistency.

Features and Benefits

The perfect shade. Its clean-white color is perfect for achieving rich printed images with greater depth and natural flesh tones.

Impressive fade resistance. Proprietary coating and fade-resistant design provide a longer shelf life for maximum value.

Uniformity. A double coating and identical finishing processes result in outstanding side-to-side uniformity and print performance.

Sturdier. Tango C2S is as much as 80% sturdier* than coated freesheet cover. That means Tango printed pieces feel more substantial and higher quality in consumers' hands, which helps strengthen brands, influence consumers and lift response rates.

Reliable. Sheet cleanliness, excellent ink lay-down and trouble-free performance, whether it's on press or finishing.

Peerless. As a true SBS, Tango single-ply paperboard is optimized with the right blend of hardwood and softwood pulp. Because it's produced at a fully integrated mill, you can count on Tango products for strength, sturdiness, runnability and visual appeal.

Responsible. All WestRock North American paperboard mills are certified to the SFI®, PEFC™ and FSC® Chain of Custody standards.† All Tango products are recyclable.

Product Uses



Entertainment and Sports Tickets
10 pt



POP Displays
10 pt-24 pt



Signage
12 pt-48 pt



Brochures
10 pt



Lottery Tickets
10 pt



Gift Cards
28 pt, 30 pt



Business Cards
14 pt, 16 pt



Photo Books
10 pt



Menus
12 pt



Direct Mail and Postcards
10 pt-18 pt



Sports and Game Cards
12 pt-24 pt



Banners
12 pt, 14 pt

Product Classifications

Product type

SBS Paperboard

Structure

Solid Bleached Sulfate
Double Clay Coated Both Sides



To learn more about Tango C2S, go to westrock.com/TangoC2S or scan here.



Tango C2S

Product Guide

Grade Availability by Caliper															Units	Method
Caliper (pts)	U.S.	◆0.010	◆0.012	0.014	0.016	0.018	0.020	0.024	0.028 [§]	0.030 [§]	0.032 [§]	0.036 [§]	0.040 [§]	0.048 [§]	inches	T-411
Thickness	Metric	254	305	356	406	457	508	610	712	763	813	915	1017	1220	microns	T-411
Nominal Basis Weight	U.S.	138	160	180	195	212	230	275	325	345	365	395	425	500	lbs/3000 sq ft (24"x36")	T-410
		83	96	108	117	128	138	166	196	208	220	238	256	301		(20"x26")
	Metric	220	260	295	320	345	375	440	529	561	594	643	691	813	gsm	T-410
Moisture		4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	4.8	percent	T-412
Smoothness																
Parker Print	Both Sides	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	μm	T-538
Stiffness																
Taber 15°	MD	60	100	135	203	245	315	470	440	540	640	800	1000	1500	gf-cm	T-489
	CD	32	50	70	95	126	165	241	230	290	350	470	530	800	gf-cm	T-489
Color																
Brightness		92	92	92	92	92	92	92	92	92	92	92	92	92	percent	T-452
CIE	L*	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	94.5	L*	CIELAB SCAN-P 72
	a*	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	1.9	a*	CIELAB SCAN-P 72
	b*	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	-8.0	b*	CIELAB SCAN-P 72

Additional Product Information

Sustainability

- Recyclable
- All WestRock North American paperboard mills are certified to the SFI[®], PEFC[™] and FSC[®] Chain of Custody standards.†
- ◆ Recycled fiber content available by specification.

Food Contact

- Meets multiple national requirements for food contact packaging, e.g., US and Canada. Contact your sales representative for information on specific markets and end uses.
- Kosher documentation available.

Environmental and Safety

- Notices under U.S. California Proposition 65 and the EU REACH are not required.
- Elemental Chlorine Free (ECF) bleached fiber.
- Meets heavy metal limits of the U.S. Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.

Quality

- Produced at an ISO 9001 certified facility.

All WestRock North American paper mills are certified to the SFI[®], PEFC[™] and FSC[®] Chain of Custody Standards. Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCOC-6S751, FSC Company Code: FSC-C104002.

† Sturdiness based on Tango C2S Taber Stiffness measure compared to coated freesheet at equivalent cover weights.

‡ Contact your WestRock sales representative for certified fiber or recycled fiber availability for Tango products.

§ Duplex structure. Contact your WestRock sales representative to learn more.

©2024 WestRock Company and/or its affiliates. WESTROCK, WestRock and Design, and the WestRock Logo are trademarks owned by WestRock Company and/or its affiliates. All rights reserved.

TPG-0224-C2



To learn more about Tango C2S, go to westrock.com/TangoC2S or scan here.

