

Premium Coated Liner (PCL)

WestRock Premium Coated Liner (PCL) is a solid bleached sulfate (SBS) sheet designed specifically for the demands of roll-fed, preprint, flexographic printing. PCL offers a smooth, bright, double clay-coated printing surface, which provides best-in-class printability for outstanding graphic reproduction. PCL also exhibits superior strength for resisting cracking and box ECT requirements.

	33	38
Grade Code	LCR077	LCR087
Conditioned Basis Wt. (7.5%H_2O), lbs/ 1000sf		
<i>Tappi T 410</i>		
Nominal	33	38
Moisture Content, %		
<i>Tappi T 412</i>		
Average (%)	6.5	6.5
Range (+/-)	1.5	1.5
SCT-CD(STFI) lb_r/in		
<i>Tappi T 826</i>		
Typical	19.2	24.0
Reject Below	16.7	18.4
Cobb 30 Minute (TOP), g/m²		
<i>Tappi T 441</i>		
Reject Above	155	155
Slide Angle, Degrees		
<i>Tappi T 815</i>		
Reject Below	22	22
Smoothness, PPS		
<i>Tappi T 555</i>		
Typical	1.6	1.6
GE Brightness, %		
<i>Tappi T 452</i>		
Typical	86	86
Gloss, %		
<i>Tappi T 480</i>		
Typical	47	47
Caliper		
<i>Tappi T 441</i>		
Points (pts)	.007	.081
Microns	178	208