WestRock

DuoDozen® 1250X

Extend your portfolio. Transform your market.


WestRock DuoDozen® 1250X offers all the power, performance and functionality of the 1250M platform, while also enabling unique package styles and configurations.

 Delivers comparably high speeds and performance to DuoDozen® 1250M, the industry standard for consistent output at high speeds

 Offers tool-less changeovers with servoenabled repeatability and auto machine prime on start up


 Enables even greater flexibility to not only accommodate different primary heights and diameters, but also new nested shapes and unique product counts








DuoDozen® 1250X



Features

- · Auto lubrication system
- · Integrated electrical panel
- · Auto machine prime



- · Light curtain safety system
- · Nordson hot melt glue system
- · Waist level carton hopper

Primary Container

- · Aluminum cans
- Height between 110mm & 159mm
- · Diameter between 57mm & 66mm

Package Formats

- Standard packs: 2x2 through 4x6
- XForm[™] (shaped) packs: 7 pack through 22 pack





Package Styles












Fridgemaster[®]

DuoDozen®

DuoWing®

Econodozen"







ArtPak

XForm™

Maximum Speeds

- 2x2 & 2x3: 300 packs/minute
- 2x6: 220 packs/minute
- 3x packs: 140 packs/minute
- 4x packs: 100 packs/minute
- XForm[™] packs: 140 packs/minute

Air & Power Requirements

- Air: 8 scfm @ 90 psi
- Power: 480V
- · Option for other power requirements as needed

Control System

- · Full servo system using Bosch motors, drives & controller
- A-B Control Logix PLC
- Touch screen HMI control panel

Changeover

 Repeatable and tool-less changeover aided by motorized positioning and HMI checklist

Note: All illustrations and specifications are subject to change without notice, and drawing dimensions are approximate and not to scale.

