

WestRock

# NatraLock® Face Seal

Hang with the dependable choice  
for blister applications.

Looking for a paperboard that can hang tough, and still look great? NatraLock® Face Seal is the reliable, durable choice for your most demanding blister packaging applications. Its ability to achieve complete fiber tear in all directions, coupled with excellent ink adhesion, gives it the perfect balance of dependable performance and striking visual appeal your brand deserves.

## Best Used With:

Beauty and Personal Care  
Media and Electronics  
Toys  
Sporting Goods  
Automotive  
Home Improvement  
Tools

## Product Classification

Solid Bleached Sulfate  
SBS  
GZ

## What You Can Expect from Us

### Sealability

Complete fiber tear in all directions provides excellent sealing and blister integrity in a wide variety of applications.

### Durability

Exceptional hang strength produces sturdy, dependable packaging that reduces unsaleables.

### Printability

A smooth surface combined with outstanding ink holdout delivers optimal printability without delamination.

### Consistency

Consistency from roll-to-roll and sheet-to-sheet make NatraLock Face Seal ideal for blister packaging applications.

## Additional Product Information

### Sustainability

Recyclable.

All WestRock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your WestRock sales representative for certified fiber availability for this product.

### Quality

Produced at an ISO 9001 certified facility.

### Environmental and Safety

Notices under US California Proposition 65 and the EU REACH regulation are not required.

Meets heavy metal limits of the US Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.

## Grade Availability & Typical Properties

## NatraLock® Face Seal

Grade Availability by Caliper					Units	Method
Caliper (pts)	U.S.	0.018	0.020	0.024	inches	T-411
Thickness	Metric	457	508	610	microns	T-411
Nominal Basis	U.S.	199	212	250	lbs/3000 sq ft	T-410
Weight	Metric	324	345	407	gsm	T-410
Moisture		5.5	5.5	5.5	percent	T-412
Brightness - WS		86	86	86	percent	T-452
<b>Color</b>						
Hunter	b	1.5	1.5	1.5	L-a-b	T-524
<b>Coated Side</b>						
Parker Print		1.2	1.2	1.2	µm	T-555
ZDT	U.S.	40	40	40	psi	T-541
	Metric	276	276	276	kPa	T-541

Values are subject to change without notice.

For more information, please contact your WestRock representative or visit our website at [westrock.com](http://westrock.com).

The information contained in this Product Guide is accurate to the best of WestRock's knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. WestRock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCCOC-6S751, FSC Company Code: FSC-C104002

© 2017 WestRock Company. WestRock® and NatraLock® are trademarks of WestRock Company. All rights reserved worldwide.

