

WestRock NatraLock® Resist+

Appealing. Safe. Functional. Sustainable.

Now there is a secure, tear-resistant, more sustainable alternative to traditional blister seal and clamshell applications. WestRock NatraLock® Resist+ features stellar graphic reproduction as well as protection from tampering while allowing heat and RF sealing on a wide range of thermoform blister materials. Uniformity and consistency from roll to roll and sheet to sheet make NatraLock Resist+ ideal for high-speed converting, filling and sealing applications. It's perfect for promotional messages, graphics and compliance information for trade seal blister packaging. With SBS and CNK offerings, NatraLock Resist+ is uniquely engineered to be used as a clamshell replacement that both deters theft and enhances sustainability.

Packaging Uses

Healthcare
Beauty and Personal Care
Media and Electronics
Toys
Sporting Goods
Automotive
Home Improvement
Tools

Product Classification

Polymer-Coated
Solid Bleached Sulfate
SBS Paperboard
Coated Natural Kraft®
CNK® Paperboard
Coated Unbleached Kraft
Laminated with Tear Resistance Film
Extruded with Heat Seal Coating

What You Can Expect from Us

Laminated Structure The rigidity of paperboard and the tear-resistance of lamination combines for unsurpassed assembly performance of trap seal blister packaging.

Heat Seal Compatibility Consistently seals to a wide variety of thermoformed blister materials, including APET, RPET, PETG, RPETG, PVC and PLA.

Low Temperature Seal Low-temperature sealing yields increased line speed, minimized risk of product damage and reduced ink degradation. With a dwell time 20% less than other hot-seal coatings, you'll see improved results and lower costs.

Product Uniformity A smooth surface, outstanding ink holdout and best-in-class consistency combine for optimal printability. Polymer coat-weight uniformity provides improved efficiencies and maximum throughput on high-speed filling equipment.

Converting Efficiency Direct printing eliminates the need to apply heat-seal coating, improving converting efficiency and reducing inventory costs.

Consistency Roll-to-roll and sheet-to-sheet consistency makes Natralock SBS ideal for high-speed converting, filling and sealing applications.

Tear Initiation Tear strength remains constant after a cut has been initiated.

Recycled Fiber Content CNK is produced with up to 15% recycled fiber, providing an option for meeting your corporate sustainability goals.

Additional Product Information

Sustainability Made with recycled fiber (CNK version). All WestRock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your WestRock sales representative for certified fiber availability for this product.

Quality Produced at an ISO 9001 certified facility.

Environmental and Safety Notices under US California Proposition 65 and the EU REACH regulation are not required. Elemental chlorine free (ECF) bleached fiber (SBS version). Meets heavy metal limits of the US Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.