

Quality you can depend on

Reliant™ Coated Cover C1S

Product Summary

Reliant cover is the ideal choice for C1S graphic and specialty packaging applications that demand reliable performance, excellent converting properties and a pleasing warm-white shade.

Features and Benefits

Superior consistency

Six Sigma manufacturing methodology coupled with a solid bleached sulfate design provides improved consistency from run to run compared to multi-ply products that utilize varied fiber sources for the middle layer.

Good ink holdout

Fully double-coated top side offers a smooth, uniform print surface that results in higher print gloss for sharper image reproduction.

Excellent converting

Solid bleached construction ensures cleaner die cutting and sheeting. It is also ideal for embossing when intricate detail is desired.

Caliper range

Available with same performance attributes, brightness and shade for 10 pt caliper up to 28 pt in rolls or skids.

Fade resistance

Proven to maintain color and shade better than competitive folding box board (FBB) imports—ideal for store signage or display applications where it is important to maintain critical brand colors.



Product Uses

- Advertising Collateral
- Store Signage
- POP Displays
- Pocket Folders
- Heavyweight Brochures
- Specialty Packaging & Inserts
- Tags & Labels
- Greeting Cards
- Book Covers
- Game Cards

Product Classifications

Product type

SBS Paperboard/GZ C1S

Structure

Solid Bleached Sulfate
Double Clay Coated One Side

Reliant™ Coated Cover C1S

Caliper	Basis Weight 24" x 36"	GSM	Gloss	Brightness	Color		
					L	a	b
10 pt	124	200	50	86	93	-0.8	1.5
12 pt	145	235	50	86	93	-0.8	1.5
14 pt	163	265	50	86	93	-0.8	1.5
15 pt	172	280	48	86	93	-0.8	1.5
16 pt	182	295	48	86	93	-0.8	1.5
18 pt	199	325	48	86	93	-0.8	1.5
20 pt	212	345	45	86	93	-0.8	1.5
24 pt	250	405	45	86	93	-0.8	1.5
26 pt	267	435	45	86	93	-0.8	1.5
28 pt	284	462	45	86	93	-0.8	1.5

All Reliant calipers are made to order from roll stock regionally; check with local merchant for availability.

Certifications

Manufacturing

- ISO 9001:2008

Forestry & Procurement

- SFI® Standards for Land Management and Wood Procurement
- SFI® Chain of Custody BV-SFICOC-US08000163
- FSC® C084429 (FSC orders require sales approval)

Food Contact

- USFDA 21 CFR 176.170 – Contact with Aqueous & Fatty Foods*
- USFDA 21 CFR 176.180 – Contact with Dry Food

Environmental & Safety

- U.S. California Proposition 65 Compliant
- CONEG Model Heavy Metal and EC/94/62 Article 11 Compliant
- ASTM F 963-95 Toy Safety, EN 71-3 European Toy Safety Compliant
- CPSC 16 CFR 1303 Lead Ban Compliant
- Elemental Chlorine Free (ECF) Bleached Fiber

*Contact WestRock for details of restrictions and/or limitations.

©2016 WestRock Company.
All rights reserved worldwide.
SFI Marks are registered marks owned
by Sustainable Forestry Initiative Inc.
FSC® is a registered trademark of the
Forest Stewardship Council®.

Printed on Reliant™ 12 pt C1S

R-PG0716-C1

501 South 5th Street
Richmond, VA 23219

westrock.com/reliant



I to Recycle

