

WestRock FoldKraft™

The natural choice when productivity matters.

If you're looking for an uncoated kraft paperboard solution that runs well and looks good, you've found it. WestRock FoldKraft™ is engineered for consistency and flatness to maximize equipment speed and minimize costly downtime. FoldKraft's market-leading smoothness delivers sharper images and excellent solid ink coverage. And, with the addition of poly coating, FoldKraft is ideal for Foodservice packaging where a grease and moisture barrier is critical. FoldKraft is the preferred choice for converters and brands, naturally.

Packaging Uses

Bakery
Drink Carriers
Dry & Refrigerated Food
Filter Frames
Foodservice Packaging
Gift Boxes
Home Goods
Office Products
Partitions
Sporting Goods

Product Classification

Uncoated
Unbleached Kraft
UUK Paperboard

What You Can Expect from Us

Productivity Maximize throughput and reduce costly equipment jams — highly consistent, lays very flat, and runs extremely clean on press with minimal fiber picking.

Printability A smooth surface for a cleaner look, sharper images and excellent solid ink coverage.

Strength and Integrity High tear strength and stiffness levels result in a strong and durable finished product.

Recycled Fiber Content Produced with up to 15% recycled fiber, providing an option for meeting corporate sustainability goals.

Additional Product Information

Sustainability Made with recycled fiber and is recyclable. All WestRock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your WestRock sales representative for certified fiber availability for this product.

Food Contact Meets multiple national requirements for food contact packaging, e.g., US and Canada. Contact your sales representative for information on specific markets and end uses.

Quality Produced at an ISO 9001 certified facility.

Environmental and Safety Notices under US California Proposition 65 and the EU REACH regulation are not required. Meets heavy metal limits of the US Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.

Grade Availability & Typical Properties (U.S.)

FoldKraft™

Grade Availability by Caliper										Units	Method
Caliper (pts)	0.013	0.015	0.016	0.018	0.020	0.022	0.024	0.026	inches	T-411	
Nominal Basis Weight	46	54	58	65	72	78	86	94	lbs/MSF	T-410	
ZDT	35	35	35	35	35	35	35	35	psi	T-541	
Elmendorf Tear											
Dry	MD	340	400	430	505	565	610	650	720	gf	T-414
	CD	350	410	450	540	600	665	725	785	gf	T-414
Stiffness											
Taber 15°	MD	120	165	215	300	400	500	600	725	gf-cm	T-489
	CD	50	70	85	130	170	215	260	315	gf-cm	T-489
Smoothness											
Sheffield	250	250	250	250	250	250	280	280	mL/min	T-538	

Grade Availability & Typical Properties (Metric)

Grade Availability by Weight										Units	Method
Thickness	330	381	406	457	508	559	610	660	microns	T-411	
Nominal Basis Weight	225	264	283	317	352	381	420	459	gsm	T-410	
ZDT	35	35	35	35	35	35	35	35	psi	T-541	
Elmendorf Tear											
Dry	MD	340	400	430	505	565	610	650	720	gf	T-414
	CD	350	410	450	540	600	665	725	785	gf	T-414
Stiffness											
Taber 15°	MD	11.8	16.2	21.1	29.4	39.2	49.0	58.8	71.1	mNm	T-489
	CD	4.9	6.7	8.3	12.7	16.7	21.1	25.5	30.9	mNm	T-489
Smoothness											
Sheffield	250	250	250	250	250	250	280	280	mL/min	T-538	

Values are subject to change without notice.

LDPE Poly Configurations Available

Thickness		
Mils (U.S.)	0.50	0.75
Microns (Metric)	12.7	19.1
Weight		
lbs/MSF (U.S.)	2.4	3.6
gsm (Metric)	11.7	17.6

Poly coating is available in P1S and P2S.
This product is Corona treated.

For more information, please contact your WestRock representative or visit our website at westrock.com.

The information contained in this Product Guide is accurate to the best of WestRock's knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. WestRock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCCOC-6S751, FSC Company Code: FSC-C104002

© 2017 WestRock Company. WestRock® and FoldKraft™ are trademarks of WestRock Company. All rights reserved worldwide.



westrock.com