Promina® Style High Performance. High Brightness.

This super-premium, single-ply SBS board is one of the brightest grades available. It uses optical brighteners within a controlled manufacturing process for ultra-white styling on both sides. WestRock Promina® Style delivers the enhanced brand perception that luxury tobacco brands demand. Yet it still offers all the performance, stiffness-to-weight and runnability advantages that make Promina the industry choice.

Packaging uses

Square Hinge Lid

Box

Rounded Corner/ Beveled Hinge Lid

Box

Display Cartons

Inner Frame

Product Classification

Solid Bleached Sulfate

SBS Paperboard

GΖ

What You Can Expect from Us

Consistency Designed and manufactured with built-in Promina performance for con-

sistent results and unparalleled efficiencies on converting equipment and

cigarette packing lines.

Runnability Converts beautifully with uniform cuts, consistent creases and excellent

emboss heights. In combination with high sheet flatness, this results in bet-

ter running blanks that enhance packer line productivity.

Styling Bright, blue-white styling for brand tobacco packaging.

Durability Promina's unique fiber mix, finishing methods and single-ply construction

contribute to cigarette packs with excellent formation, stiffness and

durability.

Fade Resistance A specialized color control delivers improved shade stability and reduces

the color reversion often associated with fluorescent whiteners.

Additional Product Information

Sustainability Recyclable.

All WestRock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your WestRock

sales representative for certified fiber availability for this product.

Food Contact Meets multiple national requirements for food contact packaging, e.g.,

US, Canada, Germany and the EU. Contact your sales representative for

information on specific markets and end uses. ISEGA Certificate for tobacco packaging available.

Quality Produced at an ISO 9001 certified facility.

Environmental and Safety

Notices under US California Proposition 65 and the EU REACH regulation

are not required.

Elemental chlorine free (ECF) bleached fiber.

Meets heavy metal limits of the US Model Toxics in Packaging rules and

Article 11 of EU Directive 94/62/EC.



Grade Availability & Typical Properties (U.S.)

Promi	na®	Sty	le
-------	-----	-----	----

Grade Availability by Ca	liper			Units	Method
Caliper (pts)		0.013	0.015	inches	T-411
Nominal Basis Weight		146	163	lbs/3000 sq ft	T-410
Moisture		5.2	5.2	percent	T-412
Internal Bond		60	60	.001 ft-lb/sq in	T-569
Stiffness					
Taber 15°	MD	97	132	gf-cm	T-489
	CD	47	65	gf-cm	T-489
GE Brightness					
Side	Wire	92	92	percent	T-452
	Felt	91	91	percent	T-452
Coated Side					
Gloss		50	50	percent	T-480
Parker Print		1.0	1.0	μm	T-555
Color					
CIE	L*	95.8	95.8	L*	SCAN-P 72:95
	a*	1.1	1.1	a*	SCAN-P 72:95
	b*	-6.8	-6.8	b*	SCAN-P 72:95

Grade Availability & Typical Properties (Metric)

didde Arandonity & Typical Froperates (metric)							
Grade Availability by Weig	Units	Method					
Thickness		330	380	microns	T-411		
Weight		238	265	gsm	T-410		
Moisture		5.2	5.2	percent	T-412		
Internal Bond		130	130	J/m2	T-569		
Stiffness							
Taber 15°	MD	9.5	12.8	mNm	T-489		
	CD	4.6	6.4	mNm	T-489		
GE Brightness							
Side	Wire	92	92	percent	T-452		
	Felt	91	91	percent	T-452		
Coated Side							
Gloss		50	50	percent	T-480		
Parker Print		1.0	1.0	μm	T-555		
Color							
CIE	L*	95.8	95.8	L*	SCAN-P 72:95		
	a*	1.1	1.1	a*	SCAN-P 72:95		
	b*	-6.8	-6.8	b*	SCAN-P 72:95		

Values are subject to change without notice.

For more information, please contact your WestRock representative or visit our website at westrock.com.

The information contained in this Product Guide is accurate to the best of WestRock's knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. WestRock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCCOC-6S751, FSC Company Code: FSC-C104002 Control of the Control of

 $@\ 2017\ WestRock\ Company.\ WestRock^{@}\ and\ Promina^{@}\ are\ trademarks\ of\ WestRock\ Company.\ All\ rights\ reserved\ worldwide.$

