

WestRock  
**ReNew100™ Classic**  
The classic answer to your  
sustainability goals.



Made from 100% recycled fiber, WestRock ReNew100™ Classic coated recycled paperboard (CRB) is the ideal solution for a wide variety of folding carton and custom applications. A double clay-coated surface provides a clean palette for eye-catching graphics. ReNew100 Classic is available in both news and kraft back.

**Packaging uses**

Cookies, Crackers,  
And Snack Foods

Cereals And Other  
Dry Foods

Toys And  
Recreational  
Products

Electronics

Household Goods

Additional Food  
And Non-Food  
Applications

**Product  
Classification**

Coated Recycled  
Paperboard

CRB Paperboard

**What You Can Expect from Us**

**Recycled Fiber  
Content**

Made from 100% recycled fiber, which has been diverted from the waste stream.

**Printability**

Double clay-coated surface for eye-catching graphics.

**Versatile Supply**

Produced at multiple mills.

**Consistency**

Excellent roll-to-roll consistency.

**Additional Product Information**

**Sustainability**

Made with 100% recycled fiber and is recyclable. All WestRock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your WestRock sales representative for certified fiber availability for this product.

**Food Contact**

Meets multiple national requirements for food contact packaging, e.g., US and Canada. Contact your sales representative for information on specific markets and end uses.

**Environmental  
and Safety**

Notices under US California Proposition 65 and the EU REACH regulation are not required. Meets heavy metal limits of the US Model Toxics in Packaging rules and Article 11 of EU Directive 94/62/EC.

## Grade Availability & Typical Properties (U.S.)

ReNew™ 100 Classic

Grade Availability by Caliper										Units	
<b>Caliper (pts)</b>	0.016	0.018	0.020	0.022	0.024	0.026	0.028	0.030	0.032	inches	
<b>Nominal Basis Weight</b>	69	77	82	88	96	104	112	120	128	lbs/MSF	
Stiffness											
<b>Taber 15°</b>	<b>MD</b>	155	225	300	395	445	540	655	790	900	gf-cm
	<b>CD</b>	55	80	100	125	145	185	220	250	300	gf-cm

## Grade Availability & Typical Properties (Metric)

Grade Availability by Weight										Units	
<b>Thickness</b>	406	457	508	559	610	660	711	762	813	microns	
<b>Nominal Basis Weight</b>	337	376	400	430	469	508	547	586	625	gsm	
Stiffness											
<b>Taber 15°</b>	<b>MD</b>	15.2	22.1	29.4	38.7	43.6	53.0	64.2	77.5	88.3	mNm
	<b>CD</b>	5.4	7.8	9.8	12.3	14.2	18.1	21.6	24.5	29.4	mNm

Values are subject to change without notice.

For more information, please contact your WestRock representative or visit our website at [westrock.com](http://westrock.com).

The information contained in this Product Guide is accurate to the best of WestRock's knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. WestRock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCCOC-6S751, FSC Company Code: FSC-C104002

© 2017 WestRock Company. WestRock® and ReNew100™ are trademarks of WestRock Company. All rights reserved worldwide.



[westrock.com](http://westrock.com)