ReNew100[™] Classic

The classic answer to your sustainability goals.

Made from 100% recycled fiber, WestRock Renew100™ Classic coated recycled paperboard (CRB) is the ideal solution for a wide variety of folding carton and custom applications. A double clay-coated surface provides a clean palette for eye-catching graphics. ReNew100 Classic is available in both news and kraft back.

Packaging uses

Cookies, Crackers, And Snack Foods

Cereals And Other

Dry Foods

Toys And Recreational Products

Electronics

Household Goods

Additional Food And Non-Food Applications

Product Classification

Coated Recycled Paperboard

CRB Paperboard

What You Can Expect from Us

Recycled Fiber Made from 100% recycled fiber, which has been diverted from

Content the waste stream.

Printability Double clay-coated surface for eye-catching graphics.

Versatile Supply Produced at multiple mills.

Consistency Excellent roll-to-roll consistency.

Additional Product Information

Sustainability Made with 100% recycled fiber and is recyclable.

All WestRock North American paperboard mills are certified to the SFI®, PEFC™, FSC™ Chain of Custody Standards. Contact your WestRock sales representative for certified fiber availability for this

product.

Food Contact Meets multiple national requirements for food contact packaging,

e.g., US and Canada. Contact your sales representative for

information on specific markets and end uses.

Environmental Notices under US California Proposition 65 and the EU REACH

and Safety regulation are not required.

Meets heavy metal limits of the US Model Toxics in Packaging rules

and Article 11 of EU Directive 94/62/EC.



Grade Availability & Typical Properties (U.S.)

ReNew™100 Classic

Grade Availability by Caliper										Units	
Caliper (pts)		0.016	0.018	0.020	0.022	0.024	0.026	0.028	0.030	0.032	inches
Nominal Basis Weight		69	77	82	88	96	104	112	120	128	lbs/MSF
Stiffness											
Taber 15°	MD	155	225	300	395	445	540	655	790	900	gf-cm
	CD	55	80	100	125	145	185	220	250	300	gf-cm

Grade Availability & Typical Properties (Metric)

Grade Availability by Weight										Units	
Thickness		406	457	508	559	610	660	711	762	813	microns
Nominal Basis Weight		337	376	400	430	469	508	547	586	625	gsm
Stiffness											
Taber 15°	MD	15.2	22.1	29.4	38.7	43.6	53.0	64.2	77.5	88.3	mNm
	CD	5.4	7.8	9.8	12.3	14.2	18.1	21.6	24.5	29.4	mNm

 $\label{lem:Values} \mbox{ Values are subject to change without notice. }$

For more information, please contact your WestRock representative or visit our website at westrock.com.

The information contained in this Product Guide is accurate to the best of WestRock's knowledge and belief. It is intended, however, only as an introduction to the typical properties of the product. WestRock disclaims any guarantee or warranty with respect to the accuracy of this information or, based on this document, with respect to the suitability of the product for any particular use, including, but not limited to, the compliance of the product with laws, regulations, or standards. This information is subject to change without notice.

Certificate Codes: SFI Certified Sourcing: NSF-SFI-CS-6S751, SFI CoC: NSF-SFICOC-6S751, PEFC: NSF-PEFCCOC-6S751, FSC Company Code: FSC-C104002

 $@\ 2017\ WestRock\ Company.\ MestRock^{\textcircled{\$}}\ and\ ReNew100^{\intercal M}\ are\ trademarks\ of\ WestRock\ Company.\ All\ rights\ reserved\ worldwide.$





