

Make a great impression

Tango[®] Coated Cover C2S

Product Summary

Superior print performance. Superior product aesthetics. Tango consistently delivers on both. Unsurpassed in its proven reputation for outstanding runnability, printability and consistency on press and through converting.

Features and Benefits

Outstanding ink holdout Printed images look richer, have greater depth and are more lifelike, for optimum visual appeal.

Better dot integrity Proprietary coating, coupled with an ultra-smooth surface, reduces dot gain so that printed images are sharper—ideal for capturing fine detail. Better dot integrity also enhances color control on press to facilitate matching to a proof in less time.

Clean-white styling Unique clean-white shade is preferred by more printers and end users to deliver crisp colors and contrast, while maintaining color fidelity on press.

Superior consistency Six Sigma manufacturing methodology coupled with a solid bleached sulfate design provides improved consistency from run to run compared to multi-ply products that utilize varied fiber sources for the middle layer.

Quality tactile feel Specialized finishing process results in a coated cover that offers greater heft, so the finished printed piece “feels” as good as it looks.

Fade resistance Paper shade is achieved using colorfast dyes to provide improved color integrity and extended shelf life for printed material.

Side-to-side uniformity Full double coating both sides and identical finishing process result in outstanding side-to-side uniformity of print performance and runability on press.



Product Uses

Signage
POP Displays
Direct Mail
Menus
Greeting Cards
Trading and Game Cards
Annual Report Covers
Brochures and Inserts
Specialty Packaging

Product Classifications

Product type

SBS Paperboard/GZ C2S
Coated Cover

Structure

Solid Bleached Sulfate
Double Clay Coated Both Sides

Tango® Coated Cover C2S

Caliper	Basis Weight 24" x 36"	Cover Weight 20" x 26"	GSM	Gloss	Brightness	Whiteness	Color		
							L	a	b
10 pt	144	87	235	51	92	122	94.5	1.9	-8.0
12 pt	167	100	270	51	92	122	94.5	1.9	-8.0
14 pt	188	113	305	51	92	122	94.5	1.9	-8.0
16 pt	203	122	330	51	92	122	94.5	1.9	-8.0
18 pt	220	132	360	51	92	122	94.5	1.9	-8.0
20 pt	240	144	390	51	92	122	94.5	1.9	-8.0
24 pt	286	172	465	51	92	122	94.5	1.9	-8.0

Certifications

Manufacturing

- ISO 9001:2008

Forestry & Procurement

- SFI® Standards for Land Management and Wood Procurement
- SFI® Chain of Custody BV-SFICOC-US08000163
- FSC® C084429 (FSC orders require sales approval)

Food Contact

- USFDA 21 CFR 176.170 – Contact with Aqueous & Fatty Foods (with restriction).
Excluding aqueous and moist foods due to optical brightener content*
- USFDA 21 CFR 176.180 – Components of Paper and Paperboard in contact with Dry Food
(without restriction)*

Environmental & Safety

- U.S. California Proposition 65 Compliant
- CONEG Model Heavy Metal and EC/94/62 Article 11 Compliant
- ASTM F 963-95 Toy Safety, EN 71-3 European Toy Safety Compliant
- CPSC 16 CFR 1303 Lead Ban Compliant
- Elemental Chlorine Free (ECF) Bleached Fiber

*Contact WestRock for details of restrictions and/or limitations.

©2016 WestRock Company.
All rights reserved worldwide.
SFI is a registered trademark of SFI Inc.
FSC is a registered trademark of the
Forest Stewardship Council.



Printed on Tango Digital C2S Coated Cover
12 pt/100# using an HP® Indigo™



T-PG0616-C2

501 South 5th Street
Richmond, VA 23219

westrock.com/tango

